

ARCTIC (H.K.) Ltd

Life Expectancy Report

Representative Test Model: S4028-6K

 \bigcirc L₁₀Expectancy: 50,000 hours minimum @ fan rated voltage and the temperature of 40°C According to the equation for Weibull distribution, MTTF \rightleftharpoons 7×L₁₀ = 350,000 hours And we rely on a zero failure Weibull test strategy and accelerated testing technique, to determine the total test time (t) for verifying the above life estimation by the equations,

$$t=1.036 \text{xMTTFx} [(B_{r;c}) \div n]^{0.91} \div A_F$$
 , and $A_F=2^{(Ts\text{-Tu})/10}$

where, $(B_{r;c})$ is Poisson distribution factor with the failure number of r equal to 0 and the decimal confidence level of c equal to 0.90(90%), and

Stress/Elevated Temperature Ts (°C)	Unstress Temperature Tu (°C)	Acceleration Factor A _F	Quantity of Test Devices n (pcs)	Possion Distribution Factor B _{r,c}	time with zero	Actual test time with zero failure t (hours)	Verified MTTE	Verified L ₁₀ (hours)
75	40	11.31	50	2.303	1,947	2,000.0	359,460	51,351

Test Progress:

rest Progress.							
Date for Test Beginning			Current Test Status			Current Total Test Time (hours)	
2022/3/1 12:00 AM	022/3/1 12:00 AM 2022/5/23 12:00 AM			✓ Termination	2000.0		
INSPECTION CRITERIA : 1.Current (Icc) variation fro		Temperature for MTTF Estimation (°C)	Acceleration Factor A _F	Estimated MTTF (hours)	Estimated L ₁₀ (hours)		
2.Rotational Speed variation 3.Acoustic variation : +/- 3		30	22.63	718,920	102,703		
4.Inspecting external if ther	40	11.31	359,460	51,351			
5.Using the lowest voltage to inspect if the fan still operates			50	5.66	179,730	25,676	
	60	2.83	89,865	12,838			
	70	1.41	44,932	6,419			
	80	0.71	22,466	3,209			
			90	0.35	11,233	1,605	

Herewith, we could assume as right on the basis of above test result. Besides, if the actual test time exceed the required, it comes out that those fans' L10 expectancy and MTTF are greater than the warrant.

Time-out for function test or others (hours)		Approved By	Review	Reported By	
	5/25/2022			Tony Choi	